




Snow Blower MSB W1500/2000

- Wide range of snow blowers available for the MX & MH range of tractors
- 2 stage rotary blower
- Snow blower is fully controlled via joystick within the Multihog cabin
- Chute can be adjusted 240° left and right using joystick, to allow blowing on left and right
- Robust and durable build
- Working widths vary from 1500 mm (5 ft) to 2000 mm (6.5 ft)

Due to our policy of continuous improvement, specifications may change subsequent to publication of this sheet.









Snow Blower MSB KFS 650/750

- High quality snow blowers for our full range of tractors
- Suitable for the hardest snow conditions
- Damage prevention via automatic overload protection & easily accessible shear pin coupling
- Open clearing system guarantees trouble-free removal of any type of snow, from slush to frozen
- Precise synchronisation permits large throwing distances & maximum performance
- Wear plate in the blower housing prevents wear from stones & chippings, saving costs
- Optional hydraulic tilt mechanism allows adjustment of blower to the road surface level
- Snow ejection chute swivels 210°
- Clearing width varies from 1300 2500 mm (51 98 in), depending on model
- Clearing height up to 1100 mm (43 in), depending on model
- Throwing range from 25 30 metres (82 99 ft)

Due to our policy of continuous improvement, specifications may change subsequent to publication of this sheet.









Snow Blower MSB Z72/Z90

- High quality snow blowers for our range of MH/MX tractors
- Ideal for high requirements and the most difficult snow conditions
- Features patented "Safety Clutch" system, which stops the blower head as soon as it comes into contact with a hard object, preventing damage to the unit
- Chute has hydraulic rotation and inclination
- Ejection chute options with 2 or 4 flaps or telescopic
- Clearing width varies from 140 270 cm (4.6 8.8 ft), depending on model
- Chute extensions are available for larger models in order to load snow onto trucks & trailers
- Ejection chute diameter of 300 mm (12 in)
- Clearing height of 90 120 cm (3 4 ft)
- Cutter diameter of 70 90 cm (28 35 in)

Due to our policy of continuous improvement, specifications may change subsequent to publication of this sheet.





